

KUBOTA GR-SERIES

GR1600 ID - GR1600 II - GR2120 - GR2120S



Excellent mowing quality under all conditions

Kubota's GR-Series ride-on mowers deliver flawless cut and collect quality, no matter what the mowing conditions. This makes them the number one choice for the demanding private user. You can select between machines with 13.5 hp or 21 hp diesel engines, equipped with mowing decks with a 107 cm or 122 cm cutting width.

Large grass collector

The large capacity grass collector is now lower. This minimizes blockages and allows you to mow for longer without having to empty it as often. Lighter materials also make handling easier.

Easy emptying and maintenance fatigue

A gas damper assists in lifting the grass collector to empty the cuttings, even when the collector is full. The flap of the hopper opens wide for easy access.

Versatile hydrostatic transmission (HST)

Kubota's proven and versatile hydrostatic transmission is easily controlled by pedal. The maximum driving speed is 10 km/h.

Well thought-out discharge channel

Flexible mowing deck

with side discharge.

The INFINITY DECK on the GR1600 ID lets you easily switch between mulching and mowing

An electronic sensor tells you when the grass collector needs to be emptied. The mower's wide discharge chute ensures a smooth flow of grass. A lever on the side of the machine is used to remove excess grass from the discharge chute without having to get off the machine.

Sprung seat and flat platform

The large and soft padded seat, with its parallel linkage suspension, can be adjusted to provide a high level of comfort for a wide variety of users. The flat operator platform provides ample legroom to reduce fatigue.

Power steering reduces fatigue

The smooth power steering on GR2120 improves maneuverability, reduces fatigue.

#Features



Great performance, even in extreme terrain

Together with four-wheel drive and power steering, the revolutionary Glide Steer system makes the GR2120 extremely agile and comfortable in all terrain conditions. To achieve a tight turning circle, the two front wheels can be turned through an incredible 70°. At maximum steering angle, the inside rear wheel rotates freely. This not only results in excellent manoeuvrability but also helps protect the lawn.



Autumn leaves firmly under control

Practical options expand the range of applications of the GR-Series ride-on mowers. For example, optimum leaf collection in the large collector hopper makes work much easier in autumn.



Low-wear drive

Unlike petrol mowers with high-wear V-belts, GR-Series mowers use PTO shafts to transmit power – just like any other professional machine. Coupled with the oil-cooled PTO clutch, this drive system is both robust and trouble-free.



Safe and smart

Proven technology redesigned: the new roll bar offers greater safety and can be easily folded down. This means that you can also mow in places where you would otherwise have to have a fully retracted roll bar.

#Technical data

Model			GR1600 ID	GR1600-II	GR2120	GR2120S
ingine						
/lodel			Z4	32	Kubota	D782
Туре		Water-cooled, 2-cylinders diesel		Water-cooled, 3-cylinders diesel		
Displacement cm ³		479		778		
Engine gross power (SAE 1995) kW/hp		10,1/13,5		15,6/21		
Maximum operating engine speed rpm		3,300-3,400		3,100-3,250		
Ingine layout	<u> </u>				zontal	,
uel tank capacity		1			18	
Dimensions		-				
Overall length		mm	1,920	2,710	2,880	2,085
Overall width with m	iover	mm	1,365	1,115	1,280	1,550
Overall height with r	ops up	mm	1,210	1,985	2,0	30
Vheelbase		mm		1,	280	
Veight (with mover	and GC, without fuel)	kg	355	450	545	470
read I	ront	mm	75	0	82	25
Ī	Rear	mm	825	800	82	20
yre size I	ront	mm	15 x 6.0-6		16 x 7.50-8	
-	Rear	mm	20.0 x 10-8		23 x 10.50-12	
ransmission						
уре				Hydrostatic	transmission	
TO			Shaft drive			
peed control		Single foot pedal				
ravelling Speed I	orward	km/h	0-1		0-9	9.0
	Reverse	km/h			5.0	
Brake					anding brake	
TO clutch		-	Mechanical w	· · · · · · · · · · · · · · · · · · ·	Hydraulic we	t multi discs
Nower deck drive		1			nt shaft	
Steering system			Mar		Full hydraulic p	ower steering
Operator's deck					lat	<u> </u>
Seat adjustment		-			lide	
Seat suspension		-			l linkage	
uel gauge		-			ndard	
lour meter					ndard	
asy checker*					ndard	
Mower OPC.					ndard	
ravel OPC.					ndard	
Blade shut off brake					n clutch	
Mower shut off whe			_	Standard	Standard	-
Grass collector				Otal Idal d	Staridard	
Capacity		1	-	370	450	-
		•		Manual with	Manual with	
Dumping system			-	gas dumping assist	gas dumping assist	-
Material of bag			-	Fabric/Steel	Fabric/Steel	-
Rops			-	i abilo/Oleei	Foldable	
iopa			-		i didable	
Mower specification	ıs					
utting width cm (inch)		106.7 (42)		121.9 (48)		
Nower system			Infinity deck (side discharge & mulching)	Direct chute	Direct chute	Side discharge
Mower blade drive				V./hexa	gonal belt	
ifting device			Mar		Hydr	aulic
Nower mounting me	ethod				attach	
Cutting height		mm		25-	-102	
Cutting height adjus	tment				Dial	
Cutting height positi	ion				11	
	Number of blades		2 3			
			'2			
	neter	m	2		1.0	

The company reserves the right to change the above specifications without notice.

This brochure is for descriptive purpose only. Please contact your local Kubota dealer for warranty information.

Kubota (U.K.) Limited

Dormer Road Thame, Oxfordshire, OX9 3UN

http://www.kubota.co.uk

This publication may not be reproduced in whole or in part in any form without the prior written consent of KUBOTA. It corresponds to the status at the time of going to press. The manufacturer reserves the right to change technical specifications without notice. Some of the parts shown in the publication are optional and are not part of the standard equipment. Information on warranty and safety as well as further product information can be obtained from the responsible KUBOTA authorized dealer.

